

# Holland®

## H-1000 FLASH-BUTT

## WELDER



## H-1000 FLASH-BUTT WELDER

### BENEFITS

- Horizontal clamp cylinder configuration
- Ability to drag/position long lengths of rail
- Welding of all rail types
- Integral automatic shearing system
- Replaceable electrode inserts lower cost of operation
- Welding of long strings of rail (up to 400 meters)

# H-1000 FLASH-BUTT WELDER



## SPECIFICATIONS

- Rated Voltage: 400 VAC Nominal
- Rated Primary Current (50% Duty Cycle): 525 Amp
- Rated Welding Current (50% Duty Cycle): 30,000 Amp
- Rated Power (50% Duty Cycle): 210 kVA
- Rated Hydraulic System Working Pressure: 207 bar (3000 PSI)
- Rated Upset Force: 1000 kN (100 Tonne)
- Rated Clamp Force: 2550 kN (255 Tonne)
- Mass: 3085kg (6800 pound)
- Overall Dimensions (Depth x Height x Width): 920 x 1170 x 1800 mm

**Holland LP**  
1000 Holland Drive  
Crete, IL. 60417

 **Holland**<sup>®</sup>

[hollandco.com](http://hollandco.com)  
[sales@hollandco.com](mailto:sales@hollandco.com)  
708.672.2300